

Type	Allgemeine Daten General data		Betriebswerte Typical operation	Grenzwerte Maximum ratings
EZ 81 Zweiweg- Gleichrichter Full-wave rectifier	Pico 9 Noval Größe 12 Outlines 12 Stift · Pin 1 a _{II} 2 — 3 k 4 f 5 f 6 — 7 a _I 8 — 9 —	$U_f = 6,3 \text{ V}$ $I_f \text{ ca. } 1 \text{ A}$ indirekt geheizt indir. heated		$U_{\text{Tr eff}} = 2 \times 250 \text{ V}$ $I = 150 \text{ mA}$ $U = 243 \text{ V}$ $R = 2 \times 150 \Omega$ $C_L = 50 \mu\text{F}$ $U_{\text{Tr eff}} = 2 \times 300 \text{ V}$ $I = 150 \text{ mA}$ $U = 293 \text{ V}$ $R = 2 \times 200 \Omega$ $C_L = 50 \mu\text{F}$ $U_{\text{Tr eff}} = 2 \times 350 \text{ V}$ $I = 150 \text{ mA}$ $U = 348 \text{ V}$ $R = 2 \times 240 \Omega$ $C_L = 50 \mu\text{F}$ $I_{\text{asp}} = 450 \text{ mA}$ $U_{f/ksp} \text{ (k pos, f neg)} = 500 \text{ V}$
				